

# 3H/2C Wi-Fi Thermostat

ST920WF



The SALUS SOLO Wi-Fi Thermostat is an economical, full featured, connected thermostat which is simple to install, configure and operate.

- Connects easily to 2.4GHz Wi-Fi networks
- Control from your phone, tablet or Alexa and Google Home devices
- Large LCD Display with Touch keys
- 5 powered relay outputs accommodate a wide variety HVAC and hydronic systems
  - 2 Heating & 2 Cooling outputs for conventional HVAC and hydronic systems
  - 3 Heating & 2 Cooling outputs for heat pump applications

## **Description and Features**

- Works with SALUS SOLO application
- Convenient commissioning with Bluetooth
- Alexa and Google Home Support
- Compact Size: 3.94" x 4.17" x 0.92" (100 mm x 106 mm x 22.5 mm)
- Large LCD Display 2.2" x 2.9" (57mm x 73mm)
- Weekday/weekend or daily schedules with 6 intervals per day
- 5 powered relay outputs for fan, heating & cooling
- Configure for conventional boiler/furnace, heat pump, or dual-fuel systems
- Optional Wire Extender (SA918) provides an easy alternative to replacing the thermostat connection wires

# **Application Overview**



# **Order Details**

3H/2C Wi-F	BH/2C Wi-Fi Thermostat				
Model	Single Unit UPC	PC Carton GTIN			
ST920WF	920WF 817989021687 10817989021684				
Wire Extender Module					
Model	Single Unit UPC	Carton GTIN			
SA918	817989024862	10817989024860			

### **Specifications**

	Controls				
	Mode touch button	Fan touch button  Down touch button			
	↑ Up touch button				
	Indicators				
Temperature		Temperature Set Point			
	Heat Mode Icon	Cool Mode Icon			
	l				

Heat Mode Icon
Cool Mode Icon
Heat/Cool/Auto
Emergency Heating
Fan Status
Keypad Locked
Day of Week
Schedule Icon
Wi-Fi Network Connected

#### **Electrical**

18-30VAC, 60Hz with, or without C-wire (switch selectable) 5 Relay outputs rated 1A @ 18-30VAC

#### **Terminals**

	Conventional AC/ Fu	rnace	<b>Heat Pump</b>	
RC	Power – Cool			
RH	Power – Heat			
C	Common			
G	Fan			
Y1	1st Stage Cooling	1st Stag	1st Stage Compressor	
Y2	2nd Stage Cooling	2nd Sta	2nd Stage Compressor	
W1/OB	1st Stage Heating	Reversing Valve		
W2/AUX	2st Stage Heating Aux/ Emergency He		nergency Heat	
L	<ul><li>Not Used</li></ul>	Check/F	Check/Fault input	
Note: Use SA918 Wire Extender if C-wire is not available.				

#### Mechanical

Weight: 0.6lb (297g)

Dimensions: 3.94"H x 4.17"W x 0.92"D (100mm x 106mm x 22.5mm)

### **Communications**

802.11 b/g/n, 2.4GHz band

Bluetooth v4.2 BR/EDR and BLE (for commissioning only)

### Environmental

Operating: 32° - 122°F (0° - 50°C), <90% RH, non-condensing Storage: 14° - 140°F (-10° - 60°C), <90% RH, non-condensing

#### **Agency Compliance**

FCC, Industry Canada RoHS Compliant

#### Warranty

5 year limited warranty

### **Compatible Devices**

SA918 Wire Extender Module

Note: Specifications are subject to change without notice

